

6.5HP Cold Paint Airless Line Striper Parking Lot Striping Tools

Basic Information

Place of Origin: ChinaBrand Name: WAGE

Certification: EMS OHSMS
 Model Number: HG-12L
 Minimum Order Quantity: 1 set

• Price: 5900-6000usd per set

Packaging Details: BoxDelivery Time: 1-3 weeks

Payment Terms:
 L/C, T/T, Western Union, MoneyGram

• Supply Ability: 10 set per week



Product Specification

Application: Road MarkingDimensions: 48 X 24 X 40 Inch

Engine Type: 4-StrokeHose Length: 50 FtPaint Capacity: 2.5 Gallon

• Paint Type: Water-based/Solvent-based

Power Source: GasolinePressure Range: 0-3000 Psi

• Product Name: Airless Line Striper

Product Type: Line StriperPump Type: DiaphragmSpray Gun: Airless

• Spray Tip Size: 0.017-0.021 Inch

Warranty: 1 YearWeight: 90 Lbs

Product Description

Airless cold paint Spraying Pavement line Striper double Guns

Airless spraying pavement road line striping marking machine two guns



Working Principle

Using gasoline engine to drive hydraulic plunger pump to form high pressure paint in the pump. The pressurized paint is transported to the airless gun through high pressure hose. Finally, the hydraulic pressure is released at the airless nozzle. After instantaneous atomization, the paint is sprayed to the ground to form a marking film layer. Normal temperature marking machine is usually suitable for the construction of underground parking spaces, plot plant area marking, a small number of pavement roads and other kinds of temperature marking.



- 1. Honda engine is used to ensure strong horsepower.
- 2. The front wheel positioning system and the vacuum pneumatic tire used in the rear wheel have good shock absorption effect, which can greatly reduce the line deformation caused by road surface fluctuation, and ensure that the marking edges and angles are neat.
- 3. The spray gun bracket can be adjusted in all directions to ensure the accuracy and convenience of line width.





5.5 HP gasoline engine

Spraying Gun

Parameter:

	HG-6L	HG-12L
power	5.5HP gasoline	6.5HP gasoline
Core pump	WAGE hydraulic piston pump	Precision Hydraulic Piston Pump
Marking mode	High pressure airless spraying	High pressure airless spraying
Working pressure	8-14Mpa	21Mpa MAX
Flow max	6L/min	12L/min
Spraying width	100-300mm(single gun)	50-500mm(DOUBLE GUNS)
Spraying thickness	0.2-0.4mm	0.2-0.4mm
Size (L*W*H)	1750*680*950mm	1700*750*1100mm
Weight	128kg	110kg

Working:





Application:



Contact:

Rita QU

Xi'an Wage Traffic Infrastructure Installation Co.,LTD

Mail: wagetraffic@hotmail.com Cell/ Whatsapp: +86 15591818803

Add:Room 401, Unit 2, Bilding 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China







rita@wagetraffic.com



wagetraffic.com

Room 401, Unit 2, Biulding 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China