



6L/Min Airless Line Striper Parking Line Striping Machine 0.5 Gpm

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: WAGE
- Certification: EMS OHSMS
- Model Number: HG-12L
- Minimum Order Quantity: 1 set
- Price: 5900-6000usd per set
- Packaging Details: Box
- Delivery Time: 1-3 weeks
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 10 set per week



Product Specification

- Amperage: 15A
- Hose Length: 50 Ft
- Hose Material: Polyurethane
- Max Flow Rate: 0.5 Gpm
- Max Pressure: 3000 Psi
- Noise Level: 68 DB
- Paint Capacity: 1 Qt
- Power Source: Electric
- Product Name: Airless Line Striper
- Product Type: Paint Sprayer
- Spray Tip Material: Stainless Steel
- Spray Tip Size: 0.017 In
- Voltage: 110V
- Warranty: 1 Year
- Weight: 25 Lbs

for more products please visit us on wagetrffic.com

Product Description

Airless cold paint Spraying Pavement line Striper double Guns

Airless spraying pavement road line striping marking machine two guns



Working Principle

Using gasoline engine to drive hydraulic plunger pump to form high pressure paint in the pump. The pressurized paint is transported to the airless gun through high pressure hose. Finally, the hydraulic pressure is released at the airless nozzle. After instantaneous atomization, the paint is sprayed to the ground to form a marking film layer. Normal temperature marking machine is usually suitable for the construction of underground parking spaces, plot plant area marking, a small number of pavement roads and other kinds of temperature marking.



1. Honda engine is used to ensure strong horsepower.
2. The front wheel positioning system and the vacuum pneumatic tire used in the rear wheel have good shock absorption effect, which can greatly reduce the line deformation caused by road surface fluctuation, and ensure that the marking edges and angles are neat.
3. The spray gun bracket can be adjusted in all directions to ensure the accuracy and convenience of line width.



5.5 HP gasoline engine



Spraying Gun

Parameter:

	HG-6L	HG-12L
power	5.5HP gasoline	6.5HP gasoline
Core pump	WAGE hydraulic piston pump	Precision Hydraulic Piston Pump
Marking mode	High pressure airless spraying	High pressure airless spraying
Working pressure	8-14Mpa	21Mpa MAX
Flow max	6L/min	12L/min
Spraying width	100-300mm(single gun)	50-500mm(DOUBLE GUNS)
Spraying thickness	0.2-0.4mm	0.2-0.4mm
Size (L*W*H)	1750*680*950mm	1700*750*1100mm
Weight	128kg	110kg

Working:



Application:



Contact:

Rita QU

[Xi'an Wage Traffic Infrastructure Installation Co.,LTD](#)

Mail: wagetrffic@hotmail.com Cell/ Whatsapp: +86 15591818803

Add:Room 401, Unit 2, Bilding 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China



Xian WAGE Traffic Infrastructure Installation Co., Ltd.



+86 15591818803



rita@wagetrffic.com



wagetrffic.com

Room 401, Unit 2, Biulding 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China