

Stainless Steel Cold Plastic Two Components Scraping Road Line Striping Marking Machine

Basic Information

Place of Origin: ChinaBrand Name: WAGE

Certification: EMS OHSMSModel Number: HG 20MM II

• Minimum Order Quantity: 1 set

• Price: 2400-2600usd per set

Packaging Details: box

• Delivery Time: 1 to 3 weeks

Payment Terms:
 L/C, T/T, Western Union, MoneyGram

Supply Ability: 10 sets per week



Product Specification

Marking Model: Two Components
Dispenser: Self Droping
Paint Cylinder Volume: 60L X2
Glass Cylinder: 25kg
Air Pressure: 0.4-0.6MPa
Capacity: 100L/min

• Dimensions: 1400*800*1100mm

• Frequency: 50Hz

Material: Stainless Steel

Power: 2.2KWPower Source: Electric

Product Name: Two Component Road Marking Machine

Spray Speed: 3-7m/minSpray Thickness: 1-4mmSpray Width: 50-400mm



More Images



Product Description

Scraping two compoent road marking machine Scraping two compoent road marking machine



General information:

two-component marking series is divided into spraying and scraping two construction processes, two coatings with the aid of two pumps or two paint barrels after mixing chemical reaction to form marking. Compared with the hot melt marking, the two-component marking construction has the advantages of environmental protection, high wear resistance, good reflectivity, long service life and easy construction.



HG-20MM-II is to put two kinds of coatings in the same barrel separated. After discharging the coatings from the tank, the coatings are fully stirred by an electric stirring shaft. After mixing in the crossing hopper, the chemical reaction is carried out. Finally, the marking is done through the crossing hopper. Compared with spraying two-component marking, scraping marking has the advantages of thicker marking thickness, longer wear resistance, better reflectivity and more uniform mixing.

Parameter:

	HG-20MM-
Marking mode	Double compartment scraping
Agitation speed	650r/min
Glass Micro sphere cylinder capacity	25kg
Spraying system	Self dropping
Paint cylinder capacity	60L/ tank x 2个cylinder
Marking thickness	1.2-2.5mm adjustment within ranges
Standard thickness	150mm
Width optional	100/200/300/400/450mm(scoops replacement)
Size (L*W*h)	1200*900*1100mm
Weight	162kg

Construction:



Contact:

Rita QU
Xi'an Wage Traffic Infrastructure Installation Co.,LTD

Mail: wagetraffic@hotmail.com Cell/ Whatsapp: +86 15591818803 Add:Room 401, Unit 2, Bilding 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China

wagetraffic.com

Room 401, Unit 2, Biulding 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China