



## Two Components 2K Convex Line Profile Line Road Marking Machine-MMA

Our Product Introduction

for more products please visit us on [wagetrffic.com](http://wagetrffic.com)

### Basic Information

- Place of Origin: China
- Brand Name: WAGE
- Certification: EMS OHSMS
- Model Number: HG-SVM
- Minimum Order Quantity: 1 set
- Price: 5000-8000usd per set
- Packaging Details: box
- Delivery Time: 1 to 3 weeks
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 10 sets per week



### Product Specification

- Marking Model: Two Components Convex Line
- Dispenser: Self Dropping
- Paint Cylinder Volume: 60L\*2
- Glass Cylinder: 25kg
- Dimensions: 1400\*800\*1100mm
- Material: Stainless Steel
- Product Name: Two Component Road Marking Machine
- Spray Thickness: 1-4mm
- Spray Width: 50-400mm
- Weight: 200kg
- Highlight: **2K convex line marking machine, MMA road marking equipment, two-component road marking machine**



### More Images



## Product Description

### Two Components 2K Convex Line Profile Line Road Marking Machine-MMA

#### Product Specifications

Attribute	Value
Marking Model	Two components convex line
Dispenser	Self dropping
Paint Cylinder Volume	60L*2
Glass Cylinder	25kg
Dimensions	1400*800*1100mm
Material	Stainless Steel
Product Name	Two Component Road Marking Machine
Spray Thickness	1-4mm
Spray Width	50-400mm
Weight	200kg

#### Product Overview

Convex line two component road line marking machine



The two-component marking series is divided into spraying and scraping two construction processes. Two coatings with the aid of two pumps or two paint barrels after mixing chemical reaction to form marking. Compared with the hot melt marking, the two-component marking construction has the advantages of:

- Environmental protection
- High wear resistance
- Good reflectivity
- Long service life
- Easy construction



HG-20MM-II puts two kinds of coatings in the same barrel separated. After discharging the coatings from the tank, the coatings are fully stirred by an electric stirring shaft. After mixing in the crossing hopper, the chemical reaction is carried out. Finally, the marking is done through the crossing hopper. Compared with spraying two-component marking, scraping marking has the advantages of:

- Thicker marking thickness
- Longer wear resistance
- Better reflectivity
- More uniform mixing

## Technical Parameters

Parameter	Specification
Marking Mode	<b>2K convex line</b>
Agitation Speed	650r/min
Glass Micro Sphere Cylinder Capacity	25kg
Spraying System	Self dropping
Paint Cylinder Capacity	60L/tank x 2
Marking Thickness	1.2-2.5mm adjustment within ranges
Standard Width	150mm
Width Optional	100/200/300/400/450mm (scoops replacement)
Size (L*W*H)	1200*900*1100mm
Weight	200kg

## Construction



### Contact Information

Rita QU

Xi'an Wage Traffic Infrastructure Installation Co.,LTD

Email: [wagetrffic@hotmail.com](mailto:wagetrffic@hotmail.com)

Cell/Whatsapp: +86 15591818803

Address: Room 401, Unit 2, Building 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China



**Xian WAGE Traffic Infrastructure Installation Co., Ltd.**



+86 15591818803



[rita@wagetrffic.com](mailto:rita@wagetrffic.com)



[wagetrffic.com](http://wagetrffic.com)

Room 401, Unit 2, Building 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China