

# Battery Driving Thermoplastic Noice Convex Line Road Marking Machine

#### **Basic Information**

Place of Origin: ChinaBrand Name: WAGE

Certification: EMS OHSMS
Model Number: HG-VM
Minimum Order Quantity: 1 set

• Price: 6200 to 9250usd

Packaging Details: box

• Delivery Time: 1 to 3 weeks

• Payment Terms: T/T, Western Union, MoneyGram, L/C

Supply Ability: 10 set per week



#### **Product Specification**

Paint Type: ThermoplasticMarking Type: Noice Marking

Paint Tank: 120LDispenser: 12kg

Bulge Thichness: 3 -5 Mm AdjustedLine Width: 15 20 30 45cm

Highlight: battery driving thermoplastic road marking

machine

, noise convex line road marking machine, thermoplastic road marking machine with

warranty



#### More Images



#### **Product Description**

battery driving Thermoplastic convex / Vibration line Road Line Marking Machine for noise marking

Vibration marking is a kind of marking which is widely used in developed countries. Its shape is concave and convex. When a car passes by, it will have a "boom" sound. It has a good warning and reminding effect on the driver, so it is also called noise markin



#### WAGE Vibration road line marking machine has the following functional:

- 1. Adopt automatic oil pressure stepless speed change driving mode, automatic walking, to ensure uniform and efficient construction effect;
- 2. The scriber adopts stainless steel insulating material coatings barrel and inserting manual mixing device to ensure the best temperature and shape of the melt.
- 3. Unique marking hopper, which makes the shape, spacing and height of marking protrusion precise and accurate, makes the marking of hot melt oscillation complete at one time, and has strong wear resistance and impact resistance.
- 4. Synchronized clutch glass bead sprayer makes the glass beads more evenly scattered on the marking line.
- 5. It is equipped with speed regulating gear shifting device and rear wheel positioning system to ensure that the equipment is fixed and straight ahead.



### Parameters:

	HG-EVM
motor	Battery
moving speed	12km/h
Grade ability	15°MAX 15°
cylinder capacity	120kg/tank
Glass Micro sphere cylinder capacity	12kg/tank
Bulge thickness	3-5mm(adjustment)
standard width	150mm
size options	150/200/300/450mm(marking scoops replacement)
size (L*W*H)mm	1400*1100*1200mm
Weight	210kg

# Main parts:



Dispenser



Liner controller



Shoe

**Battery Power** 

## **Construction spot:**



**Horizontal line marking** 



**Convex line marking** 



**Xian WAGE Traffic Infrastructure Installation Co., Ltd.** 







