

Pavement Marking Staker- Dot Maker

Our Product Introduction

for more products please visit us on wagetrffic.com

Basic Information

- Place of Origin: China
- Brand Name: WAGE
- Model Number: AT106
- Minimum Order Quantity: 1
- Price: 200
- Packaging Details: carton
- Delivery Time: 5 to 10 work days
- Payment Terms: T/T
- Supply Ability: 100 pcs/ week



Product Specification

- Body: Aluminium Alloy
- Controller: LCD
- Wheel: Circumference 300 mm
- Power: Built-in Lithium Battery
- Highlight: Pavement marking staker dot maker, Road marking dot staker machine, Dot maker for pavement marking



More Images



Product Description

Road Marking Staker (Pavement Dot Marker)



It is a positioning tool for road marking layout. It sprays marker dots on the pavement to provide reference for thermoplastic and cold-spray road marking machines, replacing traditional tape measurement and lime marking. When pushed forward, the ground-contact measuring wheel rolls on the pavement and drives the coaxial rotary encoder. Fixed pulses are output per full rotation of the wheel. The controller calculates travel distance according to pulse signals. With a fixed wheel circumference, displacement can be measured accurately. Smaller wheel delivers higher precision.

Main Applications

1. Dash line layout: Generate spaced reference dots following national standard dash line specifications (e.g. 2-4). Marking machines work along the dots to ensure solid and gap dimension compliance.
2. Special marking positioning: Layout for longitudinal deceleration lines, guide lines, rumble strips, zebra crossings and delineator positions.
3. Measuring wheel function: Distance-only mode without ink spraying for construction mileage statistics.

Components

- Encoder measuring wheel: Travel distance acquisition, wheel circumference 300 mm
- Main control board: Built-in lithium battery
- Ink jet nozzle: Sprays water-based ink (white or other colors) to make layout marks on pavement
- Ink container: Ordinary beverage bottle can be used for ink storage
- Body: Aluminium alloy foldable push rod for easy transport
- Controller: For configuration of operation parameters



Key Specifications

- Dash line setting: Custom multi-segment parameter configuration
- Distance measurement: Automatic total construction mileage counting
- Dot marking accuracy: ± 2 mm



Xian WAGE Traffic Infrastructure Installation Co., Ltd.



+86 15591818803



rita@wagetrffic.com



wagetrffic.com

Room 401, Unit 2, Biulding 2, Shenglong Plaza, Weiyang Road, Xi'an, 710016, Shaanxi, China